



NATILUOS

Unlimited Energy



PRODUCTS CATALOG

COMPLETE POWER SOLUTIONS

N
U
T
I
I



HXS6XS
HXS6XL

HXS10XS
HXS10XL

HXS15XL
HXS20XL

NUTI PRO SERIES

HXS SERIES 6KVA-20KVA

DESCRIPTION

NUTI Pro series, ranging from 6 kVA to 20 kVA, is double conversion online UPS with fully DSP controlled technology. The single phase UPS applies the advanced 3-level technology, achieving a efficiency up to 95%. With its compact design of high power density (kW=kVA), NUTI Pro series make it ideal choice for computers, telecommunication equipment and other sensitive devices.

APPLICATION

IDC(Internet Dater Center),network,servers and workstations,office etc

FEATURES

- High efficiency, up to 95%.
- kVA=kW, Output PF=1.
- 3 level of technology, compatible with complicated load.
- Battery number can be set on LCD.
- Intelligent charging management, effectively improving the life time of battery.
- Smaller size with higher power density.
- Parallel up to 4 units .
- 12A charger for option, charging for large capacity batteries.



SPECIFICATIONS

MODEL	HXS6XS	HXS6XL	HXS10XS	HXS10XL	HXS15XL	HXS20XL
Capacity	6kVA/6kW	6kVA/6kW	10kVA/10kW	10kVA/10kW	15kVA/15kW	20kVA/20kW
Phase	Single phase in , Single phase out					
Input voltage range	110Vac~288Vac					
	100% load@ > 176Vac; 90% load@ > 160Vac 80% load@ > 140Vac; 60% load@ > 110Vac					
Input THDi	≤4%@100% load; ≤6%@50% load (linear load)					
Input PF	≥0.99					
Input frequency range	40Hz-70Hz					
Output PF	1					
Output voltage	220V/230V/240V					
Voltage regulation	±1%					
THDu	≤2%(linear) ; ≤5% (non-linear)				≤1%(linear) ; ≤3% (non-linear)	
Battery voltage	192Vdc					
Battery type/number	12V,7Ah*16	External	12V,9Ah*16	External	External	
System efficiency	Normal mode: 95%					
Noise(1 meter away)	<48dB@<70%load; <58dB@>70%load				<50dB@<70%load; <58dB@>70%load	
Overload capability (Inverter mode)	110%:for 10 min ;125%:for 1min ; 150%:for 30 sec					
Overload capability (Battery mode)	110%: shut down after 1 min; 130%:shut down after 10 sec; >130%: shut down after 200 ms					
Crest factor	3:1					
Display	LED+LCD					
Interface	Standard:RS232 Optional: SNMP, USB, RS485,Dry Contacts,Parallel Kit					
W*D*H (mm)	190*426*705	190*426*336	190*485*705	190*485*336	190*485*480	
Package Weight (kg)	56	14	60	16	33	



NATILUOS

Unlimited Energy



+40 31 845 1600



info@natiluos.com
www.natiluos.com



GREEN GATE TUDOR VLADIMIRESCU 22
BLVD., SECTOR 5, BUCHAREST , ROMANIA

© All right reserved